

Monarch MFASTZL Product Usage Recommendations

The MFASTZL is a zero-lift clip, designed to be used for applications where traditional Z-Clips can't be used. These clips allow for installation and removal with zero lift-off, which can be beneficial for areas that don't have clearance.

These zero-lift clips snap together, and have a removal force of 7-10kgF minimum, which is dependent on the panel weights. The recommended spacing for clips is a minimum of 12", and a maximum of 24." This has more to do with the engagement strength between clips, and less to do with the weight of the panels.

Each application of the MFASTZL should be designed, and tested prior to installation. The design must include appropriate fasteners for each substrate, and loads should be referenced from the fastener manufacturer.

Fastener Considerations:

Hole Size: .204"/5.08mm.

Maximum Screw Head Diameter (Female): .5"/12.7mm

Maximum Screw Head Diameter (Male): .4375"/11.1mm


Countersunk Screws are Not Compatible on Female Side

Countersunk Screws are Required on Male Side

Substrate Considerations:

Both substrates should be capable of holding appropriate fasteners, and their required minimum engagement. Supporting walls should be plumb, flat, and shims should be kept to a minimum. Clips need to rest squarely on the wall, and on the panel.

Created By: amh	Approved By:	Sheet Size A	Sheet No. 1/1
Creation Date: 7/16/2024	Approval Date:	Scale	Rev



Weight:

Finish:



MONARCH
METAL INC.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MONARCH METAL FABRICATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MONARCH METAL INC. IS PROHIBITED.

New York
1700 Ocean Ave Suite 2
Ronkonkoma NY 11779
Phone: (631) 750-3000

Nevada
1080 Linda Way, Unit 10
Sparks, NV 89431
Phone: (775) 415-0100

Texas
1330 Post & Paddock St.,
Suite 800
Grand Prairie, TX 75050
(945) 202-2700

monarchmetal.com